



GERMAN TECHNOLOGY – GERMAN INNOVATION

WÜNSCHER Fahrzeugteile GmbH

Behrensallee 6 Pinneberg Germany

QUALITY CERTIFICATE

Wünscher GA 60 Automatic

Properties

GA 60 Automatic is a high-performance automatic transmission fluid developed for modern 8-speed automatic transmissions.

Its advanced formulation provides excellent load-carrying capacity and outstanding wear reduction, even under high mechanical stress. Superior friction stability ensures smooth, precise and sporty gear changes.

GA 60 Automatic delivers excellent low-temperature shifting behaviour, reliable protection against foam formation and minimal evaporation losses. High oxidation and thermal stability, combined with neutrality towards common sealing materials, ensure long service life and consistently high transmission performance.

Application notes

GA 60 Automatic is especially designed for modern ZF 6-, 8- and 9-speed automatic transmissions used in high-performance passenger vehicles.

GA 60 Automatic is **not** suitable for use in double-clutch (DCT/DSG) or continuously variable (CVT) transmissions.

Observe manufacturer's instructions!

Service description

Recommendations*:

- BMW L12108 (83 22 2 152 426)
- BMW L12108 (83 22 2 305 397)
- BMW 83 22 2 289 720 (ATF3+)
- Chrysler 68157995AA
- Honda Type 3.1
- Jaguar 02JDE 26444
- Land Rover LR 023288 / 232289
- Mopar 68157995AA
- VW / Audi G 060 162 A1/A2/A6
- VW / Audi G 055 162 (A2,A6)
- VW / Audi G 055 540 (A2)
- ZF Lifeguardfluid 8 (S671 090 312)
- ZF Lifeguardfluid 9 (AA01.500.001)

TYPICAL PARAMETERS	METHODS	UNITS	GA 60 Automatic
Density at 15°C	DIN 51 757	kg/m ³	844
Viscosity at 40°C	DIN 51 562	mm ² /s	26.9
Viscosity at 100°C	DIN 51 562	mm ² /s	5.6
Viscosity Index (VI)	DIN ISO 2909	-	157
Pour point	DIN ISO 3016	°C	-45
Flash point COC	DIN ISO 2592	°C	224
Colour	-	-	green

* meets the requirements of the OEM manufacturer
 The above values may vary within commercially accepted tolerances

December 2024